

# MT 445



## VENTILATORS

*" An independent, high-volume blowing action "*

**CONFORMS TO CE STANDARDS**

**Guarantee : 2 years – Ignition : life time guarantee**



**Model MT 445**

- High-speed smoke clearance
- Improved visibility
- Reduced temperature and toxicity
- Reduced flashover risk
- Smoke spread contained
- Shorter operation time

- ◆ Powered by **4-stroke** engine, independent.
- ◆ Ventilation by **positive pressure** (blowing action).
- ◆ **Portable, easy to handle, stable.**
- ◆ **Ergonomic.**
- ◆ **Easy to maintain.**
- ◆ Robust structure (Chassis in square profile tube, 30x30 mm)
- ◆ Low noise level.
- ◆ Engine stops automatically in the event of lack of oil.
- ◆ Fan shroud in 1.5 mm steel plate. Fan in resin, axle in aluminium.
- ◆ Protected by red epoxy coating, RAL 3000.
- ◆ Angle of operation adjustable : -5° / +20°.
- Exhaust pipe connector supplied as standard.



## FEATURES OF THE 445ERIES

Model	Reference	Accessories	Engine features	Autonomy at full speed	Dimensions L x H x W (cm)	Weight (kg)
MT 445	I60.10.011		6 CV Briggs - 4-stroke – VANGUARD Model	1 h 30	64 x 70 x 56	43
MT 445	I60.10.006	With timer	6 CV Briggs - 4-stroke – VANGUARD Model	1 h 30	64 x 70 x 56	43

Accessories : Exhaust pipe – length 2.5 m – Ref. : I60.20.012

## PERFORMANCES

Airflow at zero pressure = MT445 model : 45 000 m<sup>3</sup>/h

Test conditions: Measurement of the airflow through a 0,9m x 2m opening

